

# **High Pressure Homogenizers**



**Lab and Pilot Scale** (Process Testing)



**HL Series** (Gaulin Design)



**HLE Series** (Budget Conscious)



**HLI Series** (Integrated Drive)

## **HST** — Leading Quality and Innovation in Homogenization for Over 20 years

For more than 20 years HST has been manufacturing quality Homogenizers. They are recognized for their exceptional quality and reliability. HST stands out for its commitment to user needs, offering a unique blend of flexibility and innovative homogenization technology.

## **HOMOGENIZER STANDARD OPTIONS**

- Single or two stage homogenizing valves
- High efficiency homogenizing valves (HST MultiGapTM)
- Hydraulic or pneumatic pressure adjustment
- Sanitary or aseptic execution
- Full automated solution with Siemens or Allen Bradley control unit
- Special Ex-proofed execution according to 2014/34/EC
- Customized pumps and homogenizing valve units
- Aseptic design available on all Series
- Atex design available on all Series

## **APPLICATIONS AND PRODUCTS**

Dairy/Food/Beverages	Pharma/Chemical/Cosmetics				
Fresh milk products	Parenteral emulsions				
UHT milk products	Cell suspensions				
Baby Food	Drug delivery systems				
Ice cream	Wax/Rosin emulsions				
Egg products	Lubricant greases				
Juices and pulps	Cellulose dispersions				
Fruit concentrates	Color suspensions				
Spray drying products	Latex compounds				
Tomato products	Beauty lotions				
Enteral products	Liposomes				

## **PRODUCT OVERVIEW:**

## **LAB AND PILOT SCALE**

- The homogenization process for new products begins in the laboratory.
- These homogenizers enable the first step for a successful homogenization and provide an excellent scale up of the achieved results.

#### **HL SERIES**

- Standard series
- Gaulin design

## Capacity range:

• 5,5 - 250kW (300l/h until 35.000l/h)

## **HLE SERIES**

- · Economy series
- Aimed at the low-cost market for small capacities

### Capacity range:

• 3-75kW (10.000l/h - 200bar)

## **HLI SERIES**

- Contains an integrated drive to reduce water consumption
- · Noise insulation cladding

### **Capacity range:**

• 55-90kW (8.000 - 14.000I/h) and 400kW (up to 80.000I/h)

## **PARTS & SERVICE:**

Spare parts for homogenizers are available from our vast inventory.

We also supply spare homogenizer parts for competing brands.

**We specialize in service:** We have a service team that can repair equipment in the field at your facility. Our team is committed to providing excellent service through a system of evaluation and rebuilding equipment to factory standards.



Model		Max. Capacity (gallons per minute)								
Max. Pressure (PSI)	2,030	2,900	3,625	4,350	5,075	7,975	10,150	11,650	21,750	Max. Motor Power (hp
h and Dilat Caala										Î
b and Pilot Scale									0.04	1.5
HL1	1.25	1.25	1	0.75	0.75	0.31	0.26	0.24	0.04	4
ПЦ	1.20	1.20	-	0.75	0.75	0.31	0.20	0.24		4 ://
L Series										
HL2.5	12	8	6.5	5	4	2.5	1.3			20
HL2	24	15	14	11	8.5	5.5	2.2			50
HL3	52	37	29	24	21	13	8			75
HL4	103	70	59	50	41	23	19			200
HL5	169	114	99	83	70	41	33			270
HL6	202	136	118	101	85	48	37			340
LI Series										
HLI55	48	35	27	22	19	12	9			75
HLI75	65	47	37	31	26	16	11			100
HLI90	70	55	40	33	27	17	11			125
HLI8	275	255	210	165	150	85				500
E Series										min .
HLE3	1	1	.9	0.7	0.4	0.3	0.2	0.2	0.2	4
HLE5.5	4	2			1		.9		.4	7
HLE7.5	5	4			2		1	.5		10
HLE11	9	7		4	3	2	1	.7		15
HLE15	10	9		6	4	3	2	.9		20
HLE18.5	13	11	9	7	6	3	2	2		25
HLE22	22	18	13	11	9	9	7	4	2	2
HLE30	19	15	13	10	7	5	3	2		40
HLE37	26	22	18	13	11	7	4	3		50
HLE45	29	26	22	15	12	8	6	4		60
HLE55	44	33	24	20	18	11	7	4		74
HLE75	55	44	35	26	22	13	9	7		101

For inquiries contact Ampco Applied Products: <a href="mailto:aapgrp@ampcopumps.com">aapgrp@ampcopumps.com</a>